



| 8-5/8" TONG | STAND ALONE | WITH BACKUP |
|--------------------|---------------------------|---------------------------|
| PIPE SIZE CAPACITY | 3-1/2" - 8-5/8" (Tong) | 3-1/2" - 10-3/4" (Backup) |
| WIDTH | 38.7" (98.3 cm) | 40.8" (103.6 cm) |
| LENGTH | 57" (144.8 cm) | 58.6" (148.8 cm) |
| HEIGHT | 48.4" (122.9 cm) | 79.6" (202.2 cm) |
| WEIGHT (lb) | 1,850 (840.9 kg) | 2,950 (1341 kg) |
| RATED PRESSURE | 3000 psi | |
| RATED TORQUE | 35,000 ft-lbs (47,453 Nm) | |
| HANDLE LENGTH | 36" (91.4 cm) | |

TYPICAL TESTED PERFORMANCE (69B.35.03.33.XX)

| PRESSURE | SPEED 1 | SPEED 2 | SPEED 3 | SPEED 4 | FLOW | SPEED 1 | SPEED 2 | SPEED 3 | SPEED 4 |
|----------|---------|---------|---------|---------|------|---------|---------|---------|---------|
| | PSI | FT-LB | FT-LB | FT-LB | | FT-LB | GPM | RPM | RPM |
| 1000 | 11900 | 5900 | 2300 | 1100 | 10 | 1 | 3 | 9 | 19 |
| 2000 | 23800 | 11900 | 4700 | 2300 | 20 | 3 | 7 | 19 | 38 |
| 2250 | 26800 | 13400 | 5300 | 2600 | 40 | 7 | 15 | 38 | 77 |
| 2500 | 29800 | 14900 | 5900 | 2900 | 60 | 11 | 23 | 57 | 115 |
| 2750 | 32800 | 16400 | 6500 | 3200 | | | | | |
| 3000 | 35800 | 17900 | 7100 | 3500 | | | | | |

Disclaimer: Technical Values are +/- 5% of Listed Values

Speed 1 = Low (Hydraulic) / Low (Mechanical)

Speed 2 = High / Low

Speed 3 = Low / High

Speed 4 = High / High