



8595 SPECIFICATIONS



TYPICAL TESTED PERFORMANCE TORQUE (77.35.03.33.XX)					TYPICAL TESTED PERFORMANCE RPM (77.35.03.33.XX)				
Pressure	Speed 1	Speed 2	Speed 3	Speed 4	GPM	Speed 1	Speed 2	Speed 3	Speed 4
PSI	ft-lb	ft-lb	ft-lb	ft-lb	10	1	3	8	17
1000	12900	6400	2500	1200	20	3	6	17	34
2000	25800	12900	5100	2500	40	6	13	34	68
2250	29000	14500	5800	2900	60	10	20	51	102
2500	32200	16100	6400	3200	<p><i>Disclaimer: Technical Values are +/- 5% of Listed Values</i> <i>Speed 1 = Low (Hydraulic) / Low (Mechanical)</i> <i>Speed 2 = High / Low</i> <i>Speed 3 = Low / High</i> <i>Speed 4 = High / High</i></p>				

8595 Tong	Stand Alone	With Backup
Capacity	4-1/2" - 9-5/8" (Tong)	2-3/8" - 10-3/4" (Backup)
Width	36.2" (91.9 cm)	40.8" (103.6 cm)
Length	60" (152.4 cm)	61.6" (156.4 cm)
Height	47.25" (120.1 cm)	80.5" (204.5 cm)
Weight (lb)	1,650 (748.4 kg)	3,000 (1360.7 kg)
Hyd. System Rated Pressure	2500 psi	
Rated Torque	32,000 ft-lbs (43,386 Nm)	
Handle Length	36" (91.4 cm)	



Starr Power Tongs, LLC.
 2801 Youngsville Hwy
 Youngsville, LA 70592
 United States of America
 Phone: +1-337-330-2631